

F30AT FN-65 Long Magazine

- Powerful finish nailer for 16ga brads from 5/8" to 2 9/16"
- Switch trigger for single shot and contact actuation
- Rubber comfort grip ensures a non-slip handling and reduces vibrations and fatigue
- No-mar tip avoids marking of soft wood
- Slim nose ensures good visibility and precision
- Quick release nose for easy unjamming
- Depth control for precise countersinking
- The extra long magazine holds 150 brads for less reloading

BRAD TYPE

FN Brads (16 gauge)

TOOL TYPE



F30AT FN-65 LM

TOOL CHARACTERISTICS


Height	Width	Length	Weight
275 mm	72 mm	350 mm	2.00 kg
10.83 inch	2.84 inch	13.78 inch	4.50 lbs

Pressure 5 - 8 bar | 70 - 120 psi

Air consumption per shot 0.85 l | 0.030 SCF
Performances at 90 psi / 6.2 bar (0.62 MPa)

Lubricant Aerospace Lubricants Tribolube 12

FASTENER DATA



AxB) Shank	1.35 - 1.60 mm	0.053 - 0.062 inch
C) Head	2.90 mm	0.114 inch
L) Length	15 - 65 mm	5/8 - 2 9/16 inch
Magazine Capacity	150 brads	
Brad Type	FN Brads (16 gauge)	

NOISE VALUE

(EN 12549+A1 : 2008, EN ISO 4871 : 2009)

$L_{WA,1s}$: 92.30 dB (A) - $K_{WA,1s}$, 2.5

$L_{pA,1s}$: 87.00 dB (A) - $K_{pA,1s}$, 2.5

VIBRATION VALUE

(UNI ISO/TS 8662-11)

is below the declaration limit set by
UNI EN ISO 12100-1/2

ACTUATION & LOADING

Actuation System* Single Shot and Contact Actuation

Loading* Top Loading

*see instruction manual

APPLICATIONS

- doors and windows
- upholstery
- case backs
- sheathing
- trade shows
- kitchen units
- frame assembly
- panels and profiled boards
- mouldings and decorative trims
- boat interiors
- baseboards
- furring strips
- TV and HiFi-screens

FASCO S.R.L. Italy

Via B. Buozzi 2

I - 40057 Cadriano di Granarolo (BO)

Tel. +39 051 / 60 181 | Fax +39 051 / 766 325

fasco@fasco-spa.com | www.fasco-tools.com

FASCO
AIR DRIVEN TOOLS

MEMBER OF THE
beck
FASTENER GROUP